



FinishAdapt

FIBRE OPTIC FUSION SPLICE PROTECTOR SLEEVES


6A Midi Series TECHNICAL DATA SHEET

FinishAdapt 6A Midi Series are high quality, long-term reliability Fibre Optic Fusion Splice Protector Sleeves. Designed to restore the mechanical strength, environmental protection and optical performance of single optical fiber after fusion splicing

Single 250 - 900µm fiber. 1.9mm diameter

KEY FEATURES

- High quality and reliability with Industry Standard BELLCORE (Telcordia) single fiber range GR-1380 CORE CERTIFICATION
- Specialist Manufacturer with 24 years proven reliability
- Pre-Shrunk heat bonded design along entire length
- Single fiber entry hole for faster insertion accuracy
- Encapsulated reinforcing pin
- UL Approved high quality materials
- Compatible with most fibers, splice trays and ovens
- Over one Million 6A series held in stock



CERTIFICATIONS / REGULATORY STANDARDS

Telcordia / Bellcore
GR-1380-CORE
Single fiber range

CERTIFIED
Bellcore Test Conformance Report TCR-8
(Replaces Telcordia TA-NWT-001380)

UL224 Approved

YDPU2.E467437


RoHS Compliant
REACH Compliant
CENELEC Compliant
Conflict-Free Minerals

2011/65/EU
EC 1907/2006
European Standard EN50411-3-3
Dodd Frank Act Section 1502 Compliant



PRODUCT DIMENSIONS

Sleeve Diameter After Shrinkage	1.9 mm (0.075 inch)
Supplied Internal Diameter	1.2 mm (0.047 inch)
Fiber size	250 / 900 µm



- Heat Shrink Outer Tube
- Adhesive Inner Tube
- Stainless Steel Pin

Part Number	Sleeve Length		Inner Length		Pin Diameter		Pin Length	
	mm	inches	mm	inches	mm	inches	mm	inches
PS-6A-X15M	15.0	0.591	15.0	0.591	0.5	0.0196	15.0	0.591
PS-6A-X20M	20.0	0.787	20.0	0.787	0.5	0.0196	20.0	0.787
PS-6A-X25M	25.0	0.984	25.0	0.984	0.5	0.0196	25.0	0.984
PS-6A-X30M	30.0	1.181	30.0	1.181	0.5	0.0196	30.0	1.181
PS-6A-X40M	40.0	1.575	40.0	1.575	0.5	0.0196	40.0	1.575

All information is believed to be correct at time of publication and we reserve the right to make changes without prior notice. All dimensions nominal.

The 'Supplied Internal Diameter' refers to the internal diameter of the EVA inner tube through which the fiber is installed.


The 'Sleeve Diameter after Shrinkage' refers to the final outside diameter of the heat shrinkable outer of the sleeve after full shrinkage.

The internal EVA and external heat shrink tubing are the same length with flush ends. The pin is centred within the splice.



MATERIAL SPECIFICATION

Application Type:	Single Fiber 250 and 900µm
Compatibility:	Most splice trays, ovens and coated fibers
Outer Material:	Cross-linked Polyolefin Heat Shrinkable Tubing +135 °C MIL Spec. UL224 Approved YDPU2.E467437 & SAE-AMS-DTL-23053/5 Class 2
Inner Material:	Hot-melt adhesive Ethylene Vinyl Acetate (EVA) Copolymer
Reinforcing Pin:	Stainless Steel 302 BS 2056 with polished and rounded edges
Colours:	Clear for easy visual inspection
Splice Operating Temperature:	-40 °C to +70 °C (Heat shrink outer rated at -55 °C to +135 °C)*
Storage Temperature:	-40 °C to +70 °C
Package Quantity:	Bags of 50. Labelled over bag of 1,000



* The outer Cross-linked Polyolefin heat shrink material meets SAE-AMS-DTL-23053/5 Class 2 and has a continuous operating temperature range of -55 °C to +135 °C. However, the splice protector is designed so that the inner adhesive melts and flows first around the fiber joint at c. 65-70 °C followed by the shrinkage of the outer material. The splice protector is therefore specified with a max operating temperature of +70 °C and should not be used above this temperature otherwise it may affect the adhesive liner and damage the long-term integrity of the splice.

RECOMMENDED INSTALLATION

The product is designed so that the meltable inner melts and flows around the fibre joint followed by the outer material shrinking around the assembly. A splice oven setting of 220-225 °C for a time of 20-25 seconds is recommended to ensure the correct adhesive material flow and outer shrinkage. An additional 30 seconds cooling time should be allowed to ensure the meltable adhesive is set before handling and inserting into the splice tray.

Caution: Selecting a higher temperature or shorter cycle time may result in insufficient adhesive flow around the fiber required to form a good splice. Oven settings are based on using the industry standard Fujikura 62S and 12S fusion splicers and 40mm long PS-6A-X40M splice sleeve. The heater temperature and cycle time should be adjusted to suit the splicer oven used and the battery condition, the splice protector type and length, ambient temperature and the environmental conditions.

COMPANY BACKGROUND & EXPERIENCE

- FinishAdapt are specialists in the design, manufacture and worldwide distribution of Fusion Splice Protector Sleeves. Recognised as the industry leader with 24 years of proven quality and long-term reliability required for this specialist application. Largest range of splice sleeves available, including 1A, 2A, 3A, 3A US, 5A, 6A, dielectric, pin less, ribbon and custom manufactured.
- We worked with Bellcore (Telcordia) and British Telecom in defining the generic requirements for fusion splice protector technology. We are also joint authors of the CENELEC European Standard for splice protector product design.
- **FinishAdapt became the first and currently only company to hold Bellcore (Telcordia) GR-1380-CORE Certification.**
(Caution: most other manufacturers are not certified and can only claim compliance to this industry standard)
- Applications: laser, sensor and photonics, optical communications, fibre optic cabling in network infrastructure projects, specialist telecommunications, military, aerospace and medical industries.

PRODUCT DESIGN & ADVANTAGES

- Our splice sleeves are manufactured with a Pre-Shrunk heat-bonded assembly along the complete sleeve, encapsulating the reinforcing pin and providing a single fibre aperture. The benefit of this design eliminates fiber misalignment whilst maintaining longitudinal component alignment. The easier fibre insertion and Pre-Shrunk design results in faster installation times.
- Manufactured from high quality UL Approved Irradiation Cross-linked Polyolefin heat shrinkable outer, a unique hot-melt adhesive copolymer inner and an encapsulated stainless steel reinforcing pin with deburred and polished edges that protects the fiber from damage.
- The product is designed so that the adhesive melts and flows around the fiber joint first to provide vibration damping and environmental sealing from dust and moisture. The heat shrinkable outer then drives out any air and provides fiber retention and strain relief. The reinforcing pin provides alignment and mechanical strength.

CUSTOM & STOCK PRODUCT

A comprehensive range of Single and Mass Ribbon sleeves are available from stock. Full details are on our website. We also design and manufacture splice protection sleeves to customers requirements and own brand for leading manufacturer's and distributors globally. Please contact us now for further details and pricing.